Specifications

Model			F2690E	F2690	F3710		
			2WD		WD		
Engine							
Model			Kubota D1105	Kubota D1105	Kubota V1505T-IDI+DPF		
Туре			Liquid-cooled diesel (3 cylinder)		Liquid-cooled diesel (4 cylinder)		
Engine gross horsep	ower*	HP (kW)	24.8 (18.5) 24.8 (18.5)		36.9 (27.5)		
Total displacement		cu.in. (cm3)	68.5 (1,123)	68.5 (1,123)	91.4 (1,498)		
Air cleaner	Туре			Dual element			
	Air restriction indicator		ı	Standard			
Alternator			12	V, 40A	12 V, 60A		
Fuel tank capacity		U.S. gals. (ℓ)	16.1 (61.0)				
Transmission		•		· · ·			
Туре				HST (F2/R2)			
Max. travel speed	Forward / Reverse	mph (km/h)	12 (19.3)/6.2 (10)	12.4 (2	0)/6.8 (11)		
4WD mode select			N/A	Auto-assist 4WD with dual acting overrunning clutch/locked 4WD			
Differential lock				Standard			
Cruise control			Optional				
Tire				·			
Front			23×10.5-12	24×12-12			
Rear			16×6.5-8	18×9.5-8			
Brake				Wet discs			
Steering							
Туре			Hydrostatic power				
Tilt steering			Standard				
Turn assist brake			Optional				
Dimension							
Tread (F/R)		in. (mm)	38.4 (975) / 34.4 (875)	41.9 (1,063) / 40.2 (1,020)		
Wheel base		in. (mm)	51.2	.2 (1,300) 53.1 (1,350			
Overall length		in. (mm)	96.5	(2,450)	99.6 (2,530)		
Overall width		in. (mm)	48.8 (1,240)	53.9	(1,370)		
Overall height		in. (mm)	77.8 (1,975)	78.1	(1,985)		
Weight (without fuel)		lbs. (kg)	1,559 (707)	1,590 (721)	1,872 (849)		
Ground clearance		in. (mm)	6.9 (175)	7.3 (185)			
Mower mounting							
Туре			Independent live, Shaft drive				
PTO revolution			2,545 2,580				
Clutch			Wet multi discs, hydraulic				
Lift system			Hydraulic 2-point hitch				
Tilt angle		Degrees	90				
Tilt assist			Standard				
Weight transfer			Standard				
Others							
ROPS			Standard (ISO21299 and OSHA)				
Fuel gauge			LCD Display (Orange backlight)		LCD Display (White backlight)		
Tachometer			LCD Display (Orange backlight) LCD Display (White backlight)				
Toolbox			Standard				
TOOIDOX					Reclining suspension seat		
Seat				Reclining suspension seat			

Mower Specifications

	RCK60P-F39	RCK72P-F39	RCK60R-F36	RCK72R-F36
	Side discharge		Rear discharge	
in. (mm)	60 (1,520)	72 (1,826)	60 (1,520)	72 (1,826)
in. (mm)	1 (25)-5 (129)			
in. (mm)	Each 0.25 (6.4)			
in. (mm)	6.0 (152)		5.5 (140)	
	Welded			
in. (mm)	Top: 0.101 (4.2), Side 0,108(4.5)		0.108 (4.5)	
	3			
	Standard		N/A	
	Optional			
	in. (mm) in. (mm) in. (mm)	in. (mm) 60 (1,520) in. (mm) in. (mm) in. (mm) in. (mm) Top: 0.101 (4.2)	Side discharge in. (mm) 60 (1,520) 72 (1,826) in. (mm) 1 (25)- in. (mm) Each 0. in. (mm) 6.0 (152) Wel in. (mm) Top: 0.101 (4.2), Side 0,108(4.5)	Side discharge Rear discharge 10. (mm) 60 (1,520) 72 (1,826) 60 (1,520) 72 (1,826) 60 (1,520) 72 (1,826) 72 (1

*SAEJ199

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat bett in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: KubotaUSA.com







For Earth, For Life

F2690E/F2690/F3710

The new standard in professional front-mount mowers, the F-Series provides outstanding cutting and discharge performance. The top-of-the-line F3710 features the most powerful engine ever in a Kubota front-mount mower.





HIGH-PERFORMANCE

Get more work done in less time with Kubota's powerful diesel engines and high lifting capacity.




High lifting capacity

A high lifting capacity gives the F-Series the versatility to handle an array of implements, including a grass catcher, snow blower, rotary sweeper and debris blower.







Kubota diesel engines

Powerful Kubota diesel engines mean faster, more efficient job performance. These F-Series engines have power to spare. Their high torque rise ensures faster, smoother recovery under sudden loading, letting you power through tall or wet grass without skipping a beat. They're also comfortable and economical to operate thanks to their enhanced combustion efficiency, low vibration and noise levels.

F2690E 24.8HP/3000RPM F2690 24.8HP/3000RPM F3710 36.9HP/2500RPM



Large capacity fuel tank

A large, 16.1 gallon fuel tank not only keeps you working longer between fuel stops, it also reduces the number of fueling stops needed to complete long jobs. That means more time working and less time fueling up. The refueling pipe is now right behind ROPS.



4WD and Auto-Assist 4WD

Auto-Assist 4WD works in forward and reverse, automatically controlling the drive loads on the wheels during turns. Auto-Assist 4WD lets you turn with greater efficiency and ease with less wear and tear on the turf. Full-time 4WD can also be engaged.



Hydrostatic power steering

Hydrostatic power steering reduces operator fatigue and makes it easier to mow around trees and other obstacles.

Tilt steering wheel

The tilt steering wheel can be quickly adjusted to several positions for optimum operator comfort and further driving ease.

High/Low lever

The handy Hi/Low lever is standard equipment on all models so you can adjust the mower speed to better match the terrain or situation.



F-Series options

r-series options					
F8255	Worklight Kit (ROPS Mounted)				
F8281	Cruise Control				
F8282	Turn Assist Brakes (not compatible with cab)				
F8283	Remote Hydraulic Single Valve				
F5206	Deluxe Hard Cab				

PROFESSIONAL MOWER DECK

A durable, hard-working deck that's ready for a wide range of mowing jobs.

Pro-Commercial mower deck

The Pro-Commercial mower deck comes with an inner baffle to prevent cut grass from discharging to the front. A larger discharge chute improves discharge performance requiring less power to run the mower.

	Si disch		Rear discharge		
	60"	72"	60"	72"	
F2690E					
F2690					
F3710					



6.0" deep mower deck

Tall grass is no problem for this sidedischarge professional mower deck. Its

6.0"-deep deck design lifts tall grass so that it can be cut more efficiently. This results in a faster cut and a cleaner appearance.



PTO shaft drive

Shaft drive means no belts or pulleys – just smooth and direct power transfer from the engine to the deck and other PTO-driven attachments. Shaft drive also requires less maintenance than belt driven system and provides greater dependability.



Multi-V-belt/Steel pulleys

In addition to providing greater wear resistance, the heavy-duty cast-iron pulleys and a multi-V-belt drive system effectively distribute and reduce tension while transmitting power to the mower blades. The multi-V-belt won't twist or slip, thus reducing the chance of damage to the mower. You get more performance and power – and fewer problems.



Swivel anti-scalp wheels

The mower deck is equipped up front with two large wheels that swivel independently through 360 degrees. The wheels ensure that the deck remains above the turf, preventing unsightly turf damage.



Fabricated deck with sturdy steel construction

Stronger and more durable than conventional pressed steel decks, the F-Series' fabricated steel decks are designed to provide years of reliable cutting performance with minimal maintenance.

Rear discharge mower

When side discharge won't do, mount a rear discharge mower deck. Two sizes—60" and 72"—are available. Both decks tilt up 90 degrees for easier cleaning and blade sharpening. They also feature sturdy steel construction for greater durability and front lift arms that attach directly over the center of gravity for better control. Mulching kits are also available.



Mulching kit (option)

The professional mulching kit converts the standard deck into a highprecision mulching deck that produces an even finer mulch and sends it straight back into the turf.

SIMPLE MAINTENANCE

Designed from the ground up for fast, easy maintenance.









90-degree tilt mower deck

The mower deck lifts a full 90 degrees, providing unobstructed





Dual-element air cleaner

The dual-element air cleaner helps keep the engine running smoothly and efficiently. Only the outer filter needs to be replaced—the inner filter can be cleaned with a pressured air—helping to reduce maintenance costs. The F3710 air cleaner is equipped with a air flow prevent overheating. indicator that turns red when the filter needs cleaning or replacement.

Integrated radiator screen Digital panel

The new, easy to clean radiator screen is integrated into the engine cover to help keep the engine running cool and efficiently. A water temperature gauge and overheating alarm are also provided to help

The LCD digital panel provides vital information about the F-Series mower at a glance, including DPFrelated information (F3710 only), engine speed, remaining fuel, water temperature and hour meter. The F3710's digital panel features a battery level display to prevent unexpected downtime, as well as a white backlight for improved

Tool box

Conveniently located under the seat, the tool box provides fastaccess storage for your tools. It's also an ideal place to store your operator manual for quick and easy reference while on the job.

*Please refer to the instruction manual for details

DRIVING COMFORT

The all-important key to efficient, productive mower operation.

IMPLEMENTS

Heavy-duty options for specialized applications.





The cab has been redesigned for easy attachment and removal for all-season use.

Cab options

- Rear Worklight
- Rear View Mirror
- Heater
- Beacon Light





Deluxe seat

The F-Series' high level of comfort For easier operation and greater starts with a deluxe high-back seat with four separate adjustments—weight control, lumbar support, back angle, and seat. The lever guides have also arm rests—to provide every operator with a custom fit and optimum comfort.




Operator levers

convenience, the High/Low speed lever and deck-lifting lever are positioned beside the operator's been designed for quick, at-aglance identification.



optional rear LED work lights that improve rear visibility. And an optional flashing LED beacon is also







Snow blower



Front blade



Debris blower



Ouick-hitch



Grass catcher

* Previous grass catcher installed on the