

B2601



COMPETITIVE COMPARISON

FEATURES		Kubota B2601	Deere 2025R	Kioti CX2510	LS XJ2025H
Engine	Engine Manufacturer	Kubota	Yanmar	Daedong	Mitsubishi
	Engine	D1105-E4-D32	3TNV80F-NCJT	3A165LWH-U2	S3L2
	EPA Emission Level	Tier 4	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	25.5 (19.0)	23.9 (17.8)	24.5 (18.3)	24.4 (18.2)
	PTO HP hp (kw)	19.5 (14.5)	18 (13.4)	19.3 (14.4)	18.5 (13.8)
	Rated Engine Speeds rpm	2800	3200	2600	2500
	Aspiration	Natural	Natural	Natural	Natural
	Displacement cu. in. (liters)	61.1 (1,001)	77 (1,267)	87 (1,647)	80.4 (1,318)
	Injection Type	Indirect	Indirect	In-Line Vertical	Indirect
Fuel Tank	Cylinders	3	3	3	3
	Fuel Tank Capacity gal. (liters)	6.1 (23)	6.2 (23.5)	6.6 (25)	6.6 (25)
Transmission	Transmission	3 Range - HST	2 Range - HST	2 Range - HST	2 Range - HST
	Brakes	Multi-plate wet disc	Standard	Wet Disc	Multi-plate wet disc
	Cruise Control	Standard	Standard	Standard	N/P
Axles Steering	Differential Lock	Standard	Standard	Standard	Standard
	Power Steering	Hydraulic	Hydrostatic	Hydrostatic	Hydrostatic

B2601



COMPETITIVE COMPARISON

FEATURES		Kubota B2601	Deere 2025R	Kioti CX2510	LS XJ2025H
PTO	Type	Independent	Independent	Live	Independent
	Rear PTO Speeds @ RPM	540 @ 2800	540 @ 3200	540 @ 2600	540 @ 2500
	Mid PTO Speeds @ RPM	2500 @ 2800	2000 @ 3200	2000 @ 2600	2000 @ 2500
Hydraulic System Three Point Hitch	Main Pump Flow gpm (l/m)	4.7 (17.9)	4.0 (15.25)	N/P	5.9 (22.3)
	Power Steering Flow gpm (l/m)	3.6 (13.5)	3.5 (13.25)	N/P	2.6 (9.8)
	Total Flow gpm (l/m)	8.3 (31.4)	7.5 (28.5)	11.3 (42.9)	8.5 (32.2)
	Control Type	Open Center	Open Center	Open Center	Open Center
	Hydraulic Remote Valves	Up to 3	Up to 2	Up to 1	Up to 1
	Three Point Hitch Type	Cat 1	Cat 1	Cat 1	Cat 1
	Telescoping Link Ends	Check Chains	Check Chains	Check Chains	Check Chains
Dimensions Weight	Lift Cap, 24" Behind Lft Pts., SAE lbs. (kg)	1411 (640)	915 (415)	1203 (546)	1433 (650)
	Wheelbase in. (mm)	61.4 (1560)	63 (1600)	59.8 (1520)	59.1 (1500)
	Height (top of Cab) in. (mm)	83.9 (2130)	N/P	82.8 (2103)	85 (2150)
	Turning Radius w/o Brake ft. (m)	2WD: 8.2 (2.5) 4WD: 9.8 (3.0)	8.7 (2.65)	N/P	N/P
	Weight lb. (kg)	1566 (710)	1793 (814)	2308 (1047)	1689 (766)
Tires	Front / 4WD	R1 Ag: 7 - 12 R1 Ag: 6 - 12 R3 Turf: 22 x 8.50 - 12 R3 Turf: 23 x 8.50 - 12 R4 Ind: 23 x 8.50 - 12 R14 Ag/Ind Hybrid: 23 x 8.50 - 12	R3 Turf: 23 x 8.50 - 12 R4 Ind: 23 x 8.50 - 12 R3 Radial: 220 / 55 - R12	R1 Ag: 7.0 - 12 R3 Turf: 23 x 8.5 - 12 R4 Ind: 23 x 8.5 - 12	R3 Turf: 23 x 8.5 - 12 R4 Ind: 23 x 8.5 - 12
	Rear / 4WD	R1 Ag: 11.2 - 16 R1 Ag: 9.5 - 16 R3 Turf: 31 x 15.5 - 15 R3 Turf: 33 x 12.5 - 15 R4 Ind: 12 - 16.5 R14 Ag/Ind Hybrid: 12 - 16.5	R3 Turf: 31 x 13.50 - 15 R4 Ind: 12 - 16.5 R3 Radial: 280 / 70 - R16	R1 Ag: 11.2 - 16 R3 Turf: 33 x 12.5 - 16.5 R4 Ind: 12 - 16.5	R3 Turf: 33 x 12 - 16.5 R4 Ind: 33 x 12 - 16.5

N/A = Not Available
N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.

B2401DT



COMPETITIVE COMPARISON

FEATURES		Kubota B2401	Kioti CX2510	LS XJ2025
Engine	Engine Manufacturer	Kubota	Daedong	Mitsubishi
	Engine	D1105-E4-D32	3A165LWH-U2	S3L2
	EPA Emission Level	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	21.9 (16.3)	24.5 (18.3)	24.4 (18.2)
	PTO HP hp (kw)	19.2 (14.3)	19.3 (14.4)	18.5 (13.8)
	Rated Engine Speeds rpm	2600	2600	2500
	Aspiration	Natural	Natural	Natural
	Displacement cu. in. (liters)	68.5 (1.123)	85 (1.393)	80.4 (1.318)
	Injection Type	Indirect	Indirect	Indirect
	Cylinders	3	3	3
Fuel Tank	Fuel Tank Capacity gal. (liters)	6.1 (23)	6.6 (25)	6.6 (25)
Transmission	Transmission	Gear 9F/3R	Gear 6F/2R	Gear 6F/2R
	Brakes	Multi-plate wet disc	Wet Disk	Multi-plate wet disc
	Cruise Control	Standard	Standard	N/P
Axles Steering	Differential Lock	Standard	Standard	Standard
	Power Steering	Integral Type	Hydrostatic	Hydrostatic

B2401DT



COMPETITIVE COMPARISON

FEATURES		Kubota B2401	Kioti CX2510	LS XJ2025
PTO	Type	Transmission Driven	Transmission Driven	Independent
	Rear PTO Speeds @ RPM	540 @ 2600	540 @ 2600	540 @ 2500
	Mid PTO Speeds @ RPM	2500 @ 2600	2000 @ 2600	2000 @ 2500
Hydraulic System Three Point Hitch	Main Pump Flow gpm (l/m)	4.7 (17.9)	N/P	5.9 (22.3)
	Power Steering Flow gpm (l/m)	3.6 (13.5)	N/P	2.6 (9.8)
	Total Flow gpm (l/m)	8.3 (31.4)	11.3 (42.9)	8.5 (32.2)
	Control Type	Open Center	Open Center	Open Center
	Hydraulic Remote Valves	Up to 3	Up to 1	Up to 1
	Three Point Hitch Type	Cat 1	Cat 1	Cat 1
	Telescoping Link Ends	Check Chains	Check Chains	Check Chains
Dimensions Weight	Lift Cap, 24" Behind Lft Pts., SAE lbs. (kg)	1290 (585)	1203 (546)	1433 (650)
	Wheelbase in. (mm)	61.4 (1560)	59.8 (1520)	59.1 (1500)
	Height (top of Cab) in. (mm)	83.9 (2130)	82.8 (2103)	85 (2150)
	Turning Radius w/o Brake ft. (m)	2WD: 8.5 (2.5) 4WD: 9.2 (2.8)	N/P	N/P
	Weight lb. (kg)	1566 (710)	2260 (1025)	1689 (766)
Tires	Front / 4WD	R1 Ag: 6 - 12 R3 Turf: 22 x 8.50 - 12 R3 Turf: 23 x 8.50 - 12 R4 Ind: 23 x 8.50 - 12 R14 Ag/Ind Hybrid: 23 x 8.50 - 12	R1 Ag: 7 - 12 R3 Turf: 23 x 8.5 - 12 R4 Ind: 23 x 8.5 - 12	R3 Turf: 23 x 8.5 - 12 R4 Ind: 23 x 8.5 - 12
	Rear / 4WD	R1 Ag: 9.5 - 16 R3 Turf: 31 x 15.5 - 15 R3 Turf: 33 x 12.5 - 15 R4 Ind: 12 - 16.5 R14 Ag/Ind Hybrid: 12 - 16.5	R1 Ag: 11.2 - 16 R3 Turf: 33 x 12.5 - 16.5 R4 Ind: 12 - 16.5	R3 Turf: 33 x 12 - 16.5 R4 Ind: 33 x 12 - 16.5

N/A = Not Available
N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.



B2301

COMPETITIVE COMPARISON

FEATURES		Kubota B2301	Deere 2025R	Kiotei CX2510	LS XJ2025H
Engine	Engine Manufacturer	Kubota	Yanmar	Daedong	Mitsubishi
	Engine	D1005-E4-D32	3TNV80F-NCJT	3A165LWH-U2	S3L2
	EPA Emission Level	Tier 4	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	20.9 (15.6)	23.9 (17.8)	24.5 (18.3)	24.4 (18.2)
	PTO HP hp (kw)	17.5 (13.0)	18 (13.4)	19.3 (14.4)	18.5 (13.8)
	Rated Engine Speeds rpm	2800	3200	2600	2500
	Aspiration	Natural	Natural	Natural	Natural
	Displacement cu. in. (liters)	61.1 (1.001)	77 (1.267)	85 (1.393)	80.4 (1.318)
	Injection Type	Indirect	Indirect	Indirect	Indirect
Cylinders	3	3	3	3	
Fuel Tank	Fuel Tank Capacity gal. (liters)	6.1 (23)	6.2 (23.5)	6.6 (25)	6.6 (25)
Transmission	Transmission	3 Range - HST	2 Range - HST	2 Range - HST	2 Range - HST
	Brakes	Multi-plate wet disc	Wet Disk	Wet Disk	Multi-plate wet disc
	Cruise Control	Standard	Standard	Standard	N/P
Axles Steering	Differential Lock	Standard	Standard	Standard	Standard
	Power Steering	Hydraulic	Hydrostatic	Hydrostatic	Hydrostatic



B2301

COMPETITIVE COMPARISON

FEATURES		Kubota B2301	Deere 2025R	Kiotei CX2510	LS XJ2025H
PTO	Type	Independent	Independent	Live	Independent
	Rear PTO Speeds @ RPM	540 @ 2800	540 @ 3200	540 @ 2600	540 @ 2500
	Mid PTO Speeds @ RPM	2500 @ 2800	2000 @ 3200	2000 @ 2600	2000 @ 2500
Hydraulic System Three Point Hitch	Main Pump Flow gpm (l/m)	4.7 (17.9)	4.0 (15.25)	N/P	5.9 (22.3)
	Power Steering Flow gpm (l/m)	3.6 (13.5)	3.5 (13.25)	N/P	2.6 (9.8)
	Total Flow gpm (l/m)	8.3 (31.4)	7.5 (28.5)	11.3 (42.9)	8.5 (32.2)
	Control Type	Open Center	Open Center	Open Center	Open Center
	Hydraulic Remote Valves	Up to 3	Up to 2	Up to 1	Up to 1
	Three Point Hitch Type	Cat 1	Cat 1	Cat 1	Cat 1
	Telescoping Link Ends	Check Chains	Check Chains	Check Chains	Check Chains
Dimensions Weight	Lift Cap, 24" Behind Lft Pts., SAE lbs. (kg)	1411 (640)	915 (415)	1203 (546)	1433 (650)
	Wheelbase in. (mm)	61.4 (1560)	63 (1600)	59.8 (1520)	59.1 (1500)
	Height (top of Cab) in. (mm)	83.9 (2130)	N/P	82.8 (2103)	85 (2150)
	Turning Radius w/o Brake ft. (m)	2WD: 8.2 (2.5) 4WD: 9.8 (3.0)	8.7 (2.65)	N/P	N/P
Tires	Weight lb. (kg)	1566 (710)	1793 (814)	2260 (1025)	1689 (766)
	Front / 4WD	R1 Ag: 6 - 12 R3 Turf: 22 x 8.50 - 12 R3 Turf: 23 x 8.50 - 12 R4 Ind: 23 x 8.50 - 12 R14 Ag/Ind Hybrid: 23 x 8.50 - 12	R3 Turf: 23 x 8.50 - 12 R4 Ind: 23 x 8.50 - 12 R3 Radial: 220 / 55 - R12	R1 Ag: 7 - 12 R3 Turf: 23 x 8.5 - 12 R4 Ind: 23 x 8.5 - 12	R3 Turf: 23 x 8.5 - 12 R4 Ind: 23 x 8.5 - 12
	Rear / 4WD	R1 Ag: 9.5 - 16 R3 Turf: 31 x 15.5 - 15 R3 Turf: 33 x 12.5 - 15 R4 Ind: 12 - 16.5 R14 Ag/Ind Hybrid: 12 - 16.5	R3 Turf: 31 x 13.50 - 15 R4 Ind: 12 - 16.5 R3 Radial: 280 / 70 - R16	R1 Ag: 11.2 - 16 R3 Turf: 33 x 12.5 - 16.5 R4 Ind: 12 - 16.5	R3 Turf: 33 x 12 - 16.5 R4 Ind: 33 x 12 - 16.5

N/A = Not Available
N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.