

BX2680



COMPETITIVE COMPARISON								
FEATURES	Kubota BX2680	John Deere 1025R	Kiwi CS2510	Massey Ferguson GC1725M	LSMT125	Mahindra eMax 25L	TYM T254	
Engine	Engine Manufacturer	Kubota	Yanmar	Shibaura	Iseki	Yanmar	Kukje	Yanmar
	Engine	D1005	3TNV80F-NCJT	S773L	1.1L T4F	3TNV80F	N/P	3TNV80F
	EPA Emission Level	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	24.8 (18.5)	23.9 (17.8)	24.5 (18.3)	24.5 (18.6)	24.7 (18.17)	24.0 (18)	24 (17.8)
	PTO HP hp (kw)	19.5 (14.5)	18.0 (13.4)	19.4 (14.4)	19.6 (14.8)	17.2 (12.65)	16.9 (12.26)	17.4 (13.0)
	Rated Engine Speeds rpm	3200	3200	3000	3000	3000	2600	3000
	Aspiration	Natural	Natural	Natural	Natural	Natural	Natural	Natural
	Displacement cu. in. (liters)	61.1 (1.001)	77.3 (1.267)	69 (1.131)	N/P	68 (1.110)	71.7 (1.175)	77.3 (1.267)
	Injection Type	Indirect	Indirect	Indirect	Indirect	Indirect	Indirect	Indirect
	Cylinders	3	3	3	3	3	3	3
Fuel Tank	Alternator Amps	40	40	N/P	N/P	40	50	40
	Fuel Tank Capacity gal. (liters)	6.6 (25)	5.4 (20.4)	7.1 (26.8)	N/P	6.6 (25)	5.8 (22)	5.8 (22)
Transmission	Transmission	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range
	HST Cruise Control	Standard	Standard	Optional	Standard	Standard	N/P	N/P
	Brakes	Wet Disc	Wet Disc	Wet Multi Disc	Wet Disc	Wet Multi Disc	Wet Disc	Wet Disc
Axles Steering	Differential Lock	Rear Mechanical	Rear Mechanical	Rear Mechanical	Rear Mechanical	Rear Mechanical	N/P	N/P
	Power Steering	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic

BX2680



COMPETITIVE COMPARISON								
FEATURES	Kubota BX2680	John Deere 1025R	Kiwi CS2510	Massey Ferguson GC1725M	LSMT125	Mahindra eMax 25L	TYM T254	
PTO	Type	Live Independent	Independent	Independent	Independent	Independent	Independent	
	Rear PTO Speeds @ RPM	540 @ 3200	540 @ 3200	540 @ 3000	540 @ 3000	540 @ 3000	540 @ 3000	
Hydraulic System Three Point Hitch	Mid PTO Speeds @ RPM	2500 @ 3200	2100 @ 3200	2200 @ 3000	2000 @ 3000	2000 @ 3000	2000 @ 3000	
	Main Pump Flow gpm (l/m)	3.7 (14.0)	3.5 (13.25)	N/P	N/P	4.6 (17.4)	4.5 (17.0)	
	Power Steering Flow gpm (l/m)	2.5 (9.5)	3.5 (13.25)	N/P	N/P	2.1 (7.9)	2.6 (9.9)	
	Total Flow gpm (l/m)	6.2 (23.5)	7.0 (26.5)	6.5 (24.6)	6.8 (25.7)	6.7 (25.4)	7.1 (26.9)	
	Control Type	Position	Position	Position	Position	Position	Position	
	Hydraulic Remote Valves	Up to 2	Up to 2	Up to 1	N/P	Up to 1	Up to 1	
	Three Point Hitch Type	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I	
	Telescoping Link Ends	Check Chains	Check Chains	Check Chains	Check Chains	Check Chains	Check Chains	
	Lift Cap, 24" Behind Lft Pts., SAE lbs. (kg)	680 (310)	882 (400)	700 (318)	661 (300)	966 (438)	1323 (600)	
	Weight	1058 (480)						
Dimensions	Wheelbase in. (mm)	55.1 (2.17)	57.1 (2.25)	55.1 (2.17)	N/P	56 (2.204)	57.5 (2.26)	
	Height (top of ROPS) in. (mm)	83.1 (3.27)	86.2 (3.39)	88 (3.46)	N/P	87 (3.43)	91.3 (3.59)	
	Turning Radius w/o Brake ft. (m)	7.5 (2.3)	8.7 (2.65)	8.2 (2.54)	N/P	N/P	7.2 (2.1)	
Tires	Weight lb. (kg)	1521 (670)	1444 (665)	1485 (675)	N/P	1444 (655)	1638 (742)	
	Front / 4WD	Ag: 18x8.5-10 Turf: 18x8.5-10 Ind: 18x8.5-10 Ag/Ind Hybrid: 18x8.5-10	Turf: 23x8.50-12 Ind: 23x8.50-12	Ag: 18x8.5-10 Turf: 18x8.5-10 Ind: 18x8.5-10	Ag: 18x8.5-10 Turf: 18x8.5-10 Ind: 18x8.5-10	Ind: 18x18.5-10 Turf: 18x18.5-10	Ag: 6x12 Ind: 20x18-10 Turf: 20x8-10	Ag: 6x12 Ind: 20x18-10
	Rear / 4WD	Ag: 26x12.00-12 Turf: 26x12.00-12 Ind: 26x12.00-12 Ag/Ind Hybrid: 26x12.00-12	Turf: 31x13.5-15 Ind: 12-16.5	Ag: 26x12.0-12 Turf: 26x12.0-12 Ind: 26x12.0-12	Ag: 26x12.00-12 Turf: 26x12.00-12 Ind: 26x12.00-12	Ind: 26x12.0-12 Turf: 26x12.0-12	Ag: 9.5x16 Ind: 27x12.5-15 Turf: 29x12.5-15	Ag: 9.5x16 Ind: 27x12.5-15

N/A = Not Available
N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.

BX2380



COMPETITIVE COMPARISON								
FEATURES	Kubota BX2380	John Deere 1023E	Kiotei CS2210	Massey Ferguson MFGC1723E	LSMT122	Mahindra eMax22L	TYMT224	
Engine	Engine Manufacturer	Kubota	Yanmar	Shibaura	Iseki	Yanmar	Kukje	Yanmar
	Engine	D902	3TNM74F-NCJT	S773L-F21	1.1L T4F	3TNV76F	N/P	3TNM74F
	EPA Emission Level	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	21.6 (16.1)	22.4 (16.5)	21.1 (15.7)	22.5 (16.8)	21.5 (16)	22.0 (16.4)	21.5 (16)
	PTO HP hp (kw)	17.7 (13.2)	14.5 (10.8)	18.6 (13.9)	18.7 (13.9)	15 (11.2)	14.9 (11.1)	N/A
	Rated Engine Speeds rpm	3200	3200	3000	2600	3000	2600	3000
	Aspiration	Natural	Natural	Natural	Natural	Natural	Natural	Natural
	Displacement cu. in. (liters)	54.8 (0.898)	60.6 (0.993)	69 (0.1131)	68.35 (1.12)	68 (1.11)	71.7 (1.175)	60.6 (0.993)
	Injection Type	Indirect	Indirect	Indirect	Indirect	Indirect	Indirect	Indirect
	Cylinders	3	3	3	3	3	3	3
	Alternator Amps	40	40	N/P	N/P	40	50	40
Fuel Tank	Fuel Tank Capacity gal. (liters)	6.6 (25)	5.6 (21.2)	6.7 (25.5)	6.6 (25)	6.6 (25)	5.8 (22)	6.6 (25)
Transmission	Transmission	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range
	HST Cruise Control	Standard	N/A	Optional	Standard	Standard	N/P	N/P
	Brakes	Wet Disc	Wet Disc	Wet Multi Disc	Wet Disc	Wet Multi Disc	Wet Disc	Wet Disc
Axles Steering	Differential Lock	Rear Mechanical	Rear Mechanical	Rear Mechanical	Rear Mechanical	Rear Mechanical	N/P	N/P
	Power Steering	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic

BX2380



COMPETITIVE COMPARISON								
FEATURES	Kubota BX2380	John Deere 1023E	Kiotei CS2210	Massey Ferguson MFGC1723E	LSMT122	Mahindra eMax22L	TYMT224	
PTO	Type	Live Independent	Independent	Independent	Independent	Independent	Independent	
	Rear PTO Speeds @ RPM	540 @ 3200	540 @ 3200	540 @ 3000	540 @ 2600	540 @ 3000	540 @ 2550	540 @ 3000
	Mid PTO Speeds @ RPM	2500 @ 3200	2100 @ 3200	2200 @ 3000	2000 @ 2600	2000 @ 3000	2000 @ 2550	2500 @ 3000
Hydraulic System Three Point Hitch	Main Pump Flow gpm (l/m)	3.7 (14.0)	3.5 (13.2)	N/A	2.0 (7.5)	4.6 (17.4)	4.5 (17.0)	4.17 (15.8)
	Power Steering Flow gpm (l/m)	2.5 (9.5)	2.8 (10.8)	N/A	4.3 (15.5)	2.1 (7.9)	7.1 (26.9)	2.11 (8.0)
	Total Flow gpm (l/m)	6.2 (23.5)	6.3 (24.0)	6.5 (24.6)	6.3 (23.0)	6.7 (25.3)	11.6 (43.9)	6.97 (26.4)
	Control Type	Position	Position	Position	Position	Position	Position	Position
	Hydraulic Remote Valves	Up to 2	Up to 2	Up to 1	N/P	Up to 1	Up to 1	N/A
	Three Point Hitch Type	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I
Dimensions Weight	Lift Cap. 24" Behind Lft Pts., SAE lbs. (kg)	680 (310)	681 (309)	700 (318)	661 (300)	966 (438)	1323 (600)	679 (308)
	Wheelbase in. (mm)	55.1 (2.17)	57.1 (2.25)	55.1 (2.17)	N/P	56 (2.204)	57.5 (2.26)	53.1 (2.09)
	Height (top of ROPS) in. (mm)	83.1 (2110)	86.2 (3.39)	88 (3.46)	N/P	87 (3.43)	91.3 (3.59)	86.6 (3.41)
	Turning Radius w/o Brake ft. (m)	7.5 (2.3)	7.4 (2.25)	N/P	N/P	N/P	7.2 (2.1)	8.3 (2.5)
	Weight lb. (kg)	1443 (650)	1345 (610)	1485 (675)	1433 (650)	1444 (655)	1638 (742)	1433 (650)
Tires	Front / 4WD	Ag: 18x8.5-10 Turf: 18x8.5-10 Ind: 18x8.5-10 Ag/Ind Hybrid: 18x8.5-10	Turf: 18 x 8.50- 10 Ind: 18x8.5-10	Ag: 18x8.5-10 Turf: 18x8.5-10 Ind: 18x8.5-10	Ag: 18x8.5-10 Turf: 18x8.5-10 Ind: 18x8.5-10	Turf: 18x8.5-10 Ind: 18x8.5-10	Ag: 6x12 Ind: 20x18-10 Turf: 20x18-10	Bar: 16x8.5-8 Turf: 16x7.5-8
	Rear / 4WD	Ag: 26x12.00-12 Turf: 26x12.00-12 Ind: 26x12.00-12 Ag/Ind Hybrid: 26x12.00- 12	Turf: 26x12-12 Ind: 26x12-12	Ag: 26x12.00-12 Turf: 26x12.00-12 Ind: 26x12.00-12	Ag: 26x12.00-12 Turf: 26x12.00-12 Ind: 26x12.00-12	Turf: 26x12.0-12 Ind: 26x12.0-12	Ag: 9.5x16 Ind: 27x12.5-15 Turf: 29x12.5-15	Bar: 24x12.0-12 Turf: 24x12.0-12

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.



COMPETITIVE COMPARISON						
FEATURES		Kubota BX1880	MahindraeMax20S	John Deere 1023E	KioteiCS2210	LSMT122
Engine	Engine Manufacturer	Kubota	Yanmar	Yanmar	Shibaura	Yanmar
	Engine	D722	N/P	3TNM74F-NCJT	S773L-F21	3TNV76F
	EPA Emission Level	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	16.6 (12.4)	19.4 (14.5)	22.4 (16.5)	21.1 (15.7)	21.5 (16)
	PTO HP hp (kw)	13.7 (10.2)	14.2 (10.6)	14.5 (10.8)	18.6 (13.9)	15 (11.2)
	Rated Engine Speeds rpm	3200	3000	3200	3000	3000
	Aspiration	Natural	Natural	Natural	Natural	Natural
	Displacement cu. in. (liters)	43.9 (0.719)	60.6 (0.993)	60.6 (0.993)	69 (0.1131)	68 (1.11)
	Injection Type	Indirect	Indirect	Indirect	Indirect	Indirect
	Cylinders	3	3	3	3	3
	Alternator Amps	40	45	40	N/P	40
Fuel Tank	Fuel Tank Capacity gal. (liters)	6.6 (25)	6.6 (25)	5.6 (21.2)	6.7 (25.5)	6.6 (25)
Transmission	Transmission	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range
	HST Cruise Control	Optional	N/P	N/A	Optional	Standard
	Brakes	Wet Disc	Wet Disc	Wet Disc	Wet Multi Disc	Wet Multi Disc
Axles Steering	Differential Lock	Rear Mechanical	N/P	Rear Mechanical	Rear Mechanical	Rear Mechanical
	Power Steering	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic



COMPETITIVE COMPARISON						
FEATURES		Kubota BX1880	MahindraeMax20S	John Deere 1023E	KioteiCS2210	LSMT122
PTO	Type	Live Independent	Independent	Independent	Independent	Independent
	Rear PTO Speeds @ RPM	540 @ 3200	540 @ 2550	540 @ 3200	540 @ 3000	540 @ 3000
	Mid PTO Speeds @ RPM	2500 @ 3200	2000 @ 2550	2100 @ 3200	2200 @ 3000	2000 @ 3000
Hydraulic System Three Point Hitch	Main Pump Flow gpm (l/m)	3.7 (14.0)	4.1 (15.5)	3.5 (13.2)	N/P	4.6 (17.4)
	Power Steering Flow gpm (l/m)	2.5 (9.5)	6.2 (23.4)	2.8 (10.8)	N/P	2.1 (7.9)
	Total Flow gpm (l/m)	6.2 (23.5)	10.3 (38.9)	6.3 (24.0)	6.5 (24.6)	6.7 (25.3)
	Control Type	Position	Position	Position	Position	Position
	Hydraulic Remote Valves	Up to 2	Up to 1	Up to 2	Up to 1	Up to 1
	Three Point Hitch Type	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I
Dimensions Weight	Lift Cap, 24" Behind Lft Pts., SAE lbs. (kg)	680 (310)	680 (309)	681 (309)	700 (318)	966 (438)
	Wheelbase in. (mm)	55.1 (2.17)	53.1 (2.09)	57.1 (2.25)	55.1 (2.17)	56 (2.204)
	Height (top of ROPS) in. (mm)	81.9 (3.22)	86.6 (3.41)	86.2 (3.39)	88 (3.46)	87 (3.43)
	Turning Radius w/o Brake ft. (m)	7.5 (2.3)	7.2 (2.1)	7.4 (2.25)	N/P	N/P
Tires	Weight lb. (kg)	1404 (637)	1499 (680)	1345 (610)	1485 (675)	1444 (655)
	Front / 4WD	Turf: 16x7.5-8 Ind: 16x7.5-8	Ag: 18 x 8.5-10 Turf: 18 x 8.5-10 Ind: 18 x 8.5-10	Turf: 18 x 8.50-10 Ind: 18x8.5-10	Ag: 18x8.5-10 Turf: 18x8.5-10 Ind: 18x8.5-10	Turf: 18x8.5-10 Ind: 18x8.5-10
	Rear / 4WD	Turf: 24x12-12 Ind: 24x12-12	Ag: 26 x 12-12 Turf: 26 x 12-12 Ind: 26 x 12-12	Turf: 26x12-12 Ind: 26x12-12	Ag: 26x12.00-12 Turf: 26x12.00-12 Ind: 26x12.00-12	Turf: 26x12.0-12 Ind: 26x12.0-12

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.

BX23S



COMPETITIVE COMPARISON								
FEATURES	Kubota BX23S	John Deere1025R	KiotiCS2510	Massey Ferguson GC1725M	LSMT125	Mahindra eMax 25L	TYM T254	
Engine	Engine Manufacturer	Kubota	Yanmar	Shibaura	Iseki	Yanmar	Kukje	Yanmar
	Engine	D902	3TNV80FR-NCJT	S773L	1.1L T4F	3TNV80F	N/P	3TNV80F
	EPA Emission Level	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	21.6 (16.1)	23.9 (17.8)	24.5 (18.3)	24.5 (18.6)	24.7 (18.2)	24.0 (18)	24 (17.8)
	PTO HP hp (kw)	17.7 (13.2)	18.0 (13.4)	19.4 (14.4)	19.6 (14.8)	17.2 (12.7)	16.9 (12.26)	17.4 (13.0)
	Rated Engine Speeds rpm	3200	3200	3000	3000	3000	2600	3000
	Aspiration	Natural	Natural	Natural	Natural	Natural	Natural	Natural
	Displacement cu. in. (liters)	54.8 (.898)	77.3 (1.267)	69 (1.131)	N/P	77.3 (1.110)	71.7 (1.175)	77.3 (1.267)
	Injection Type	Indirect	Indirect	Indirect	Indirect	Indirect	Indirect	Indirect
	Cylinders	3	3	3	3	3	3	3
	Alternator Amps	40	40	N/P	N/P	40	50	40
	Fuel Tank	Fuel Tank Capacity gal. (liters)	6.6 (25)	5.6 (21.2)	7.1 (26.8)	N/P	6.6 (25)	5.8 (22)
Transmission	Transmission	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range	HST - 2 Range
	HST Cruise Control	Standard	Standard	Optional	Standard	Standard	N/P	N/P
	Brakes	Wet Disc	Wet Disc	Wet Multi Disc	Wet Disc	Wet Multi Disc	Wet Disc	Wet Disc
Axles Steering	Differential Lock	Rear Mechanical	Rear Mechanical	Rear Mechanical	Rear Mechanical	Rear Mechanical	N/P	N/P
	Power Steering	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic

Kubota Tractor

BX23S



COMPETITIVE COMPARISON								
FEATURES	Kubota BX23S	John Deere1025R	KiotiCS2510	Massey Ferguson GC1725MB	LSMT125	Mahindra eMax 25L	TYM T254	
PTO	Type	Live Independent	Independent	Independent	Independent	Independent	Independent	
	Rear PTO Speeds @ RPM	540 @ 3200	540 @ 3200	540 @ 3000	540 @ 3000	540 @ 3000	540 @ 3000	
	Mid PTO Speeds @ RPM	2500 @ 3200	2100 @ 3200	2200 @ 3000	2000 @ 3000	2000 @ 3000	2550 @ 2600	2000 @ 3000
Hydraulic System Three Point Hitch	Main Pump Flow gpm (l/m)	3.7 (14.0)	3.5 (13.2)	N/P	N/P	4.6 (17.4)	4.18 (15.8)	
	Power Steering Flow gpm (l/m)	2.5 (9.5)	3.5 (13.2)	N/P	N/P	2.1 (7.9)	2.77 (10.5)	
	Total Flow gpm (l/m)	6.2 (23.5)	7.0 (26.4)	6.5 (24.6)	6.8 (25.7)	6.7 (25.4)	7.1 (26.9)	6.95 (26.3)
	Control Type	Position	Position	Position	Position	Position	Position	Position
	Hydraulic Remote Valves	Up to 2	Up to 2	Up to 1	N/P	Up to 1	Up to 1	Up to 1
	Three Point Hitch Type	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I
	Telescoping Link Ends	Check Chains	Check Chains	Check Chains	Check Chains	Check Chains	Check Chains	Check Chains
	Lift Cap, 24" Behind Lft Pts., SAE lbs. (kg)	Optional	681 (309)	700 (318)	661 (300)	966 (438)	1323 (600)	1058 (480)
Dimensions Weight	Wheelbase in. (mm)	55.1 (2.17)	57.1 (145)	55.1 (2.17)	N/P	56 (2.204)	57.5 (2.26)	57.5 (2.26)
	Height (top of ROPS) in. (mm)	86.2 (3.39)	86.2 (3.39)	88 (3.46)	N/P	87 (3.43)	91.3 (3.59)	91.3 (3.59)
	Turning Radius w/o Brake ft. (m)	7.5 (2.3)	7.4 (2.25)	8.2 (2.54)	N/P	N/P	7.2 (2.21)	8.3 (2.5)
	Weight lb. (kg)	1570 (712)	1444 (655)	1485 (675)	N/P	1444 (655)	1638 (742)	1610 (730)
Tires	Front / 4WD	Turf: 18x8.5-10 Ind: 18x8.5-10 Ag/Ind Hybrid: 18x8.5-10	Turf: 23x8.50-12 Ind: 23x8.50-12	Ag: 18x8.5-10 Turf: 18x8.5-10 Ind: 18x8.5-10	Ag: 18x8.5-10 Turf: 18x8.5-10 Ind: 18x8.5-10	Ind: 18x18.5-10 Turf: 18x18.5-10	Ag: 6x12 Ind: 20x18-10 Turf: 20x8-10	Ag: 6x12 Ind: 20x18-10
	Rear / 4WD	Turf: 26x12-12 Ind: 26x12-12 Ag/Ind Hybrid: 26x12-12	Turf: 31x13.5-15 Ind: 12-16.5	Ag: 26x12.0-12 Turf: 26x12.0-12 Ind: 26x12.0-12	Ag: 26x12.00-12 Turf: 26x12.00-12 Ind: 26x12.00-12	Ind: 26x12.0-12 Turf: 26x12.0-12	Ag: 9.5x16 Ind: 27x12.5-15 Turf: 29x12.5-15	Ag: 9.5x16 Ind: 27x12.5-15

NA = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.