

FEATURE			KUBOTA KX057-5	Bobcat E55	Cat 305.5E2 CR L/Arm	Deere 60G	Takeuchi TB260
Engine	Model		Kubota V2607	---	Cat C2.4	Yanmar 4TNV98	Yanmar 4TNV86CT
	Horsepower (*SAE J 1995 Gross)	HP / rpm	47.6 / 2200*	49.7 / 2200	45.7 / 2200	53 / 2000	47.6 / 2400
	Displacement	cu. in.	159.6	---	146.0	203.0	127.6
	Emissions Tier Level (EPA)		Tier 4 Final	Tier 4	Tier 4 Final	Tier 4 Final	Tier 4 Final
Dimension	Overall length	in.	217.3	206.0	215.0	227.0	218.5
	Overall height	in.	100.4	100.0	100.0	100	102.4
	Overall width	in.	77.2	77.2	78.0	79	78.7
	Tail swing type		Conventional	Conventional	Minimal	Conventional	Conventional
	Tail swing overhang	in.	11.4	13.4	4.0	16.5	11.8
	Minimum ground clearance	in.	12.2	---	---	13.0	13.1
Working range	Maximum digging height	in.	226.0	230.3	220.0	235	233.9
	Maximum dumping height	in.	164.6	162.7	161	164.0	166.1
	Maximum digging radius at ground	in.	240.6	243.7	237.0	---	242.5
	Maximum digging depth	in.	152.2	154.5	152.0	150.8	153.5
	Maximum vertical digging depth	in.	67.3	126.0	107	---	117.3
Hydraulic System	Pump capacity	GPM	39.4	36.6	39.6	38	45.3
	Number of hydraulic pumps		3	1	---	1	4
	Auxiliary hydraulic line flow rate	GPM	19.8	20.0	21.1	24.2	27.0
	Auxiliary relief	psi	2490	3045	2734	---	---
	Maximum arm crowd force	lbf	5,644	5,751	5,575	6,989	5,752
Maximum bucket breakout force	lbf	11,177	8,977	11,445	9,237	12,756	
Drive system	Maximum traveling speed	mph	1.8 / 3.1	1.9 / 3.1	1.7 / 2.8	1.8 / 3.0	1.7 / 3.0
	Maximum traction force	lbf	14,480	---	10,746	---	13,997
	Under carriage shoe width	in.	15.7	15.7	15.7	15.7	15.7
	Ground pressure	psi	4.5	4.8	4.5	5.12	4.51
Swing system	Unit swing speed	rpm	9.3	9.0	10.0	9.5	9.4
	Boom swing angle	degree	70 / 55	75 / 50	60 / 50	80 / 60	78 / 55
Blade	Blade width x height	in.	77.2 x 16.1	77.2 x 17.6"	78 x 14.8	79 X 16.0	16.9
	Maximum lift above ground	in.	17.3	15.1	16	18	16.9
	Maximum drop below ground	in.	16.1	18.3	22.0	15	16.9
Capacities	Fuel reservoir	gal.	19.8	21.1	16.6	31.7	20.8
	Hydraulic reservoir / system	gal.	11.9 / 20.9	4.0 / 14.5	18.0 / 20.6	21.1 / ---	12.9 / 23.8
Operating weight	Rubber tracks, canopy	lbs.	12,200	12,004	11,596	13547 w/cab	12,509

These comparison of specifications are based upon the most reliable data obtainable by Kubota at the time of publication.