



L4060HST-LE/L4060HSTC-LE

COMPETITIVE COMPARISON							
FEATURES	L4060-LE	Deere 3039R	Kioti DK4210SE	Kioti CK4010SE	LS XR4140H	Massey Ferguson 1840M	
Engine	Engine Manufacturer	Kubota	Yanmar	Daedong	Daedong	N/P	Iseki
	Engine	V2403-CR-E4	3TNV86C-MJT	3H-TH4D	3H-TH4B	L3C19-T	N/P
	EPA Emission Level	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	42 (31.3)	38.7 (28.5)	39.6 (29.5)	39.6 (29.5)	40 (29.8)	39.4 (29.4)
	PTO HP hp (kw)	32.5 (24.2)	31.1 (23.2)	29.1 (21.7)	33.3 (24.8)	32 (23.5)	27.9 (20.8)
	Rated Engine Speeds rpm	2600	2600	2600	2600	2600	2600
	Aspiration	Natural with EGR	Turbocharged	Natural	Natural	Natural	Turbocharged
	Displacement cu. in. (liters)	148.5 (2434)	95.7 (1.57)	111.4 (1.826)	111.4 (1.826)	114.7 (1.88)	N/P
	Injection Type	Direct	Direct	In-Line	In-Line	Vertical Water-Cooled	Direct
	Cylinders	4	3	3	3	3	3
Fuel Tank	Alternator Amps	ROPS: 40 CAB: 60	75	N/P	N/P	70	N/P
	Fuel Tank Capacity gal. (liters)	13.5 (51)	ROPS: 10 (37.4) CAB: 12.6 (47.6)	12.7 (48)	9 (34)	ROPS: 10.6 (40.1) CAB: 12.4 (46.9)	10.6 (40.1)
Transmission	Transmission	HST Plus: 3 Range	eHST: 3 Range	HST: 3 Range	HST: 3 Range	HST: 3 Range	HST: 3 Range
	Brakes	Wet disc type	Multi-plate Wet Disc	Wet Disc	Wet Disc	Multi-plate Wet Disc	Sealed Wet Disc
Axles Steering	Differential Lock	Standard	Standard	Standard	Standard	Standard	Standard
	Power Steering	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic

Kubota Tractor



L4060HST-LE/L4060HSTC-LE

COMPETITIVE COMPARISON							
FEATURES	L4060-LE	Deere 3039R	Kioti DK4210SE	Kioti CK4010SE	LS XR4140H	Massey Ferguson 1840M	
PTO	Type	Independent	Independent	Independent	Independent	Independent	
	Rear PTO Speeds @ RPM	540 @ 2600	540 @ 2600	540 @ 2600	540 @ 2600	540 @ 2600	
	Mid PTO Speeds @ RPM	2000 @ 2600	2100 @ 2600	2000 @ 2600	2000 @ 2600	2000 @ 2600	
Hydraulic System Three Point Hitch	Clutch Type	Hydraulic	Wet Disc	Hydraulic	Hydraulic	Position/Draft	
	Engagement Method	Electro-hydraulic	Electro-hydraulic	Manual	Manual	Manual	
	Main Pump Flow gpm (l/m)	9.4 (35.6)	6.2 (23.5)	N/P	N/P	8.2 (31)	
	Power Steering Flow gpm (l/m)	4.7 (17.9)	9.1 (34.3)	N/P	N/P	5.5 (20.8)	
	Total Flow gpm (l/m)	14.1 (53.5)	15.3 (57.8)	16.5 (62.4)	11.7 (44.4)	13.7 (51.9)	
	Control Type	Position	Open Center	Position	Position	Position	
Dimensions Weight	Hydraulic Remote Valves	Up to 3	Up to 3	Up to 2	Up to 4	Up to 3	
	Three Point Hitch Type	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	
	Lower Link Ends	Telescopic Lower Links	Rigid Lower Links	Rigid Lower Links	Telescopic Lower Links	Telescopic Lower Links	
	Lift Cap. 24" Behind Lift Pts., SAE lbs. (kg)	2760 (1250)	2194 (995)	2716 (1232)	1631 (740)	2755 (1250)	
	Wheelbase in. (mm)	74.6 (1895)	68 (1727)	71.3 (1810)	65.7 (1670)	73.2 (1859)	
	Height in. (mm)	ROPS: 97.6 (2480) CAB: 91.1 (2315)	ROPS: 93.3 (2360) CAB: 85 (2150)	ROPS: 96.8 (2458) CAB: 93 (2363)	ROPS: 99.2 (2520) CAB: 91.7 (2330)	ROPS: 93 (2362) CAB: 90 (2286)	
Tires	Turning Radius w/o Brake ft. (m)	8.9 (2.7)	9.2 (2.8)	N/P	N/P	N/P	
	Weight lb. (kg)	ROPS: 3748 (1700) CAB: 4134 (1875)	ROPS: 2900 (1315.4) CAB: 3570 (1619.3)	ROPS: 3523 (1598) CAB: 4043 (1834)	ROPS: 2921 (1325) CAB: 3397 (1541)	ROPS: 3935 (1785) CAB: 4446 (2017)	
	Front / 4WD	R1 Ag: 8.3 - 16 R3 Turf: 27 x 8.50 - 15 R3 Turf: 27 x 10.50 - 15 R3 Turf: 29 x 12.50 - 15 R4 Ind: 10 - 16.5	R1 Ag: 7 - 14 R3 Turf: 27 x 8.50 - 15 R3 Turf: 25 / 10.5LL x 15 R4 Ind: 25 x 8.5 - 14 R4 Ind: 27 x 8.5 - 15	R1 Ag: 8 - 16 R3 Turf: 29 - 12.5 - 15 R4 Ind: 10 - 16.5	R1 Ag: 7 - 16 R3 Turf: 25 x 8.5 - 15 R4 Ind: 27 x 8.5 - 15	R1 Ag: 9.5 - 16 R3 Turf: 28 x 8.5 - 15 R4 Ind: 12 - 16.5	R1 Ag: 8 - 16 R3 Turf: 27 x 8.50 - 15 R4 Ind: 10 - 16.5 R4 Ind: 10 - 16.5 R4 Ind: 25 x 8.5 - 14 R4 Snow: 250 / 75
	Rear / 4WD	R1 Ag: 14.9 - 24 R3 Turf: 355 / 80 D20 R3 Turf: 41 x 18LL - 16.1 R3 Turf: 44 x 18 - 20 R4 Ind: 17.5L - 24	R1 Ag: 11.2 - 24 R3 Turf: 41 x 14 - 20 R3 Turf: 41 x 18LL - 16.1 R4 Ind: 15 - 19.5 R4 Ind: 43 x 16 - 20	R1 Ag: 13.6 - 24 R3 Turf: 21.5L - 16.1 R4 Ind: 14.9 - 24	R1 Ag: 11.2 - 24 R3 Turf: 41 x 14 - 20/4 R4 Ind: 15 - 19.5	R1 Ag: 13.6 - 24 R3 Turf: 41 x 14 - 20 R4 Ind: 17.5L - 24	R1 Ag: 13.6 - 24 R3 Turf: 41 x 14.00 - 20 R4 Ind: 14.9 - 24 R4 Ind: 17.5L - 24 R4 Ind: 15 - 19.5 R4 Snow: 400 / 80

NA = Not Available
NP = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.