

# RA1042T Single Rotary Rake



COMPETITIVE COMPARISON								
FEATURE	KUBOTA RA1042T	Krone Swadro 42T	Kuhn GA 4221 GTH	New Holland ProRotor 3114	Massey Ferguson RK3824	Pequea HR1140	The Kubota Advantage	
Specs	Working Width	13'9"	13'9"	13'5"	12'10"	13'5"		
	Transport Width	6'7"	11'2"	6'5"	6'7"	6'	5'11"	Safe Transport Width
	Length	12'1"	16'3"	13'6"	12'1"	11'4"	N/P	Compact length for easier storage
	Number of Rotors	1	1	1	1	1	1	
	Number of Tine Arms	11	13	11	11	12	11	
	Number of Tines Per Arm	4	4	4	4	4	4	
	Straight or Curved Tine Arms	Curved	Straight	Straight	Curved	Straight	Straight	Higher Lift out of Windrow
	Easily Removed Tine Arms	No Tools Required	No	Yes	Yes	Yes	Yes	Quickly and easily transportable
	Suggested PTO	20	31	20	20	41	40	Very low HP Requirements
	Turn Direction of Rotor	Counter clockwise	Counter Clockwise	Clockwise	Counter Clockwise	Clockwise	Counter Clockwise	
Gearbox	Virtually Maintenance Free Oil Bath	Greased	Grease	Oil Bath	Greased	Oil Bath	Always running in a bath of oil for endless lubrication	
Carriage	Lift Height	19.7"	24"	N/P	N/P	N/P	N/P	
	Carriage Pushed or Pulled	Pulled	Pushed	Pushed	Pulled	Pushed	Pulled	More easily follows ground than pushed models
	Tandem Axle	Standard	Standard	Standard	Standard	Optional	Standard	
	360 Degree Axle Rotation	Yes	No	No	Yes	No	No	Ability to completely rotate axles
	Weight (lbs.)	1256	1720	1377	1256	1190	1550	No unnecessary extra weight
	Hitch Type	Drawbar	Drawbar	Drawbar	Drawbar	Drawbar	Drawbar	Drawbar

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.