

<b>ASHLAND®</b>		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Kubota® SAE 15W-40 KUBOTA # 70000-10005  
ENGINE OIL

### Recommended use of the chemical and restrictions on use

<b>Details of the supplier of the safety data sheet</b> Ashland P.O. Box 2219 Columbus, OH 43216 United States of America  EHS Customer Requests@ashland.com	<b>Emergency telephone number</b> 1-800-ASHLAND (1-800-274-5263)  <b>Regulatory Information Number</b> 1-800-325-3751  <b>Product Information</b> 614-790-3333
--	---


## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Eye irritation : Category 2A

Reproductive toxicity : Category 2

### GHS Label element

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : Causes serious eye irritation.  
Suspected of damaging fertility or the unborn child.

Precautionary Statements : **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Wash skin thoroughly after handling.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**

<b>ASHLAND®</b>		Page: 2
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention.  
If eye irritation persists: Get medical advice/ attention.

**Storage:**  
Store locked up.

**Disposal:**  
Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components**

Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	8.30
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	1.62
ZINC DIALKYL DITHIOPHOSPHATE	93819-94-4	Skin Irrit. 2; H315 Eye Dam. 1; H318	1.11
DODECYLPHENOL, MIXED ISOMERS	121158-58-5	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Repr. 2; H361 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0.16

<b>ASHLAND®</b>		Page: 3
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

---

#### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Obtain medical attention.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)  
Causes serious eye irritation.  
Suspected of damaging fertility or the unborn child.
- Notes to physician : No hazards which require special first aid measures.

<b>ASHLAND®</b>		Page: 4
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

---

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons  
hydrogen sulfide  
zinc oxide  
Sulphur oxides  
mercaptans
- Specific extinguishing methods :  
  
Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

<b>ASHLAND®</b>		Page: 5
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

Other information : Comply with all applicable federal, state, and local regulations.

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Container hazardous when empty.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	PEL	500 ppm 2,000 mg/m <sup>3</sup>	OSHA_TRA NS
		REL	5 mg/m <sup>3</sup> Mist.	NIOSH/GUID E
		STEL	10 mg/m <sup>3</sup> Mist.	NIOSH/GUID E
		PEL	5 mg/m <sup>3</sup> Mist.	OSHA_TRA NS
		TWA	5 mg/m <sup>3</sup> Mist.	Z1A
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	400 ppm 1,600 mg/m <sup>3</sup>	Z1A
		REL	5 mg/m <sup>3</sup> Mist.	NIOSH/GUID E
		STEL	10 mg/m <sup>3</sup> Mist.	NIOSH/GUID E
		PEL	5 mg/m <sup>3</sup>	OSHA_TRA

<b>ASHLAND</b>		Page: 6
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

			Mist.	NS
--	--	--	-------	----

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:  
impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : liquid  
 Odour : No data available  
 Odour Threshold : No data available  
 pH : No data available  
 Melting point/freezing point : No data available  
 Boiling point/boiling range : No data available

<b>ASHLAND®</b>		Page: 7
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

Flash point : > 390 °F / > 199 °C  
Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)  
GLP: Calculated Explosive Limit

Lower explosion limit : 1 %(V)  
GLP: Calculated Explosive Limit

Vapour pressure : 0.055 hPa (20 °C)  
Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)  
Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

<b>ASHLAND®</b>		Page: 8
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide  
Hydrocarbons  
hydrogen sulfide  
Sulphur oxides  
zinc oxide fumes  
mercaptans

**SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

**Acute toxicity**

Not classified based on available information.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg

ZINC DIALKYLDITHIOPHOSPHATE:

Acute oral toxicity : LD 50 (Rat): 2,600 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks: May cause skin irritation in susceptible persons.

Result: Repeated exposure may cause skin dryness or cracking.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Mildly irritating to skin

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

ZINC DIALKYLDITHIOPHOSPHATE:

Result: Irritating to skin

DODECYLPHENOL, MIXED ISOMERS:

Result: Irritating to skin



<b>ASHLAND®</b>		Page: 9
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Mildly irritating to eyes

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to eyes

ZINC DIALKYLDITHIOPHOSPHATE:

Result: Corrosive to eyes

DODECYLPHENOL, MIXED ISOMERS:

Result: Irritating to eyes

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

**Components:**

DODECYLPHENOL, MIXED ISOMERS:

Reproductive toxicity - : Suspected of damaging fertility.

Assessment

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks: No data available

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

<b>ASHLAND®</b>		Page: 10
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

ZINC DIALKYLDITHIOPHOSPHATE:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l  
Exposure time: 96 h  
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): 5.4 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae : EC 50 (Selenastrum capricornutum (green algae)): 2.1 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test

DODECYLPHENOL, MIXED ISOMERS:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**Persistence and degradability**

ZINC DIALKYLDITHIOPHOSPHATE:

Biodegradability : Biodegradation: 1.5 %  
Exposure time: 28 d  
Remarks: Not readily biodegradable.

**Bioaccumulative potential**

ZINC DIALKYLDITHIOPHOSPHATE:

Partition coefficient: n- : log Pow: 0.59 - 1.2 (23 °C)

<b>ASHLAND</b>		Page: 11
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

octanol/water

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
  
Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods
---------------------

**U.S. DOT - RAIL**

Not dangerous goods
---------------------

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods
---------------------

**SAFETY DATA SHEET**

Revision Date: 05/22/2015

Print Date: 6/9/2015

SDS Number: 000000205480

Kubota® SAE 15W-40 KUBOTA # 70000-10005  
ENGINE OIL

Version: 1.0

KU10005

**TRANSPORT CANADA - ROAD**

Not dangerous goods

**TRANSPORT CANADA - RAIL**

Not dangerous goods

**TRANSPORT CANADA - INLAND WATERWAYS**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES**

Not dangerous goods

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ARSENIC	7440-38-2	1	62500

<b>ASHLAND</b>		Page: 13
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

**SARA 311/312 Hazards** : Acute Health Hazard  
Chronic Health Hazard

**SARA 313 Component(s)**

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL]BIS(DITHIOPHOS PATE)	93819-94-4	1.11 %
---	------------	--------

**Pennsylvania Right To Know**

HEAVY PARAFFINIC DISTILLATE	64742-54-7	90.00 - 100.00 %
LUBRICANT ADDITIVE	Not Assigned	10.00 - 20.00 %
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	5.00 - 10.00 %
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	1.00 - 5.00 %

**New Jersey Right To Know**

HEAVY PARAFFINIC DISTILLATE	64742-54-7	90.00 - 100.00 %
LUBRICANT ADDITIVE	Not Assigned	10.00 - 20.00 %
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	5.00 - 10.00 %
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	1.00 - 5.00 %
ZINC DIALKYL DITHIOPHOSPHATE	93819-94-4	1.00 - 5.00 %

**California Prop 65** Proposition 65 warnings are not required for this product based on the results of a risk assessment.

**The components of this product are reported in the following inventories:**

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AUSTR : On the inventory, or in compliance with the inventory
- NZIOC : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECL : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory

<b>ASHLAND®</b>		Page: 14
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

IECSC : On the inventory, or in compliance with the inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 05/22/2015

<p><b>NFPA:</b></p> <p style="text-align: center;">Special hazard.</p>	<p><b>HMIS III:</b></p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>2</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow; color: black;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>2</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>2</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**  
Combustible Liquid Class IIIB

**Full text of H-Statements referred to under sections 2 and 3.**

- H304                    May be fatal if swallowed and enters airways.
- H315                    Causes skin irritation.
- H318                    Causes serious eye damage.
- H319                    Causes serious eye irritation.
- H361                    Suspected of damaging fertility or the unborn child.
- H400                    Very toxic to aquatic life.
- H410                    Very toxic to aquatic life with long lasting effects.

Sources of key data used to compile the Safety Data Sheet  
 Ashland internal data including own and sponsored test reports  
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the

<b>ASHLAND®</b>		Page: 15
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/9/2015
		SDS Number: 000000205480
Kubota® SAE 15W-40 KUBOTA # 70000-10005 ENGINE OIL		Version: 1.0
KU10005		

information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
 BEI : Biological Exposure Index  
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
 FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System