Safety Data Sheet

Printing date 10/05/2016 Revised On 10/05/2016

1 Identification of the substance and manufacturer

Trade name: **BRAKE & PARTS CLEANER**

Product code: 77700-05575

Product category PC35 Washing and cleaning products (including solvent based products)

Seymour of Sycamore Manufacturer/Supplier: 917 Crosby Avenue Sycamore, IL 60178 phone: 815-895-9101

www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. No smoking. **Precautionary statements**

Keep away from heat/sparks/open flames/not surfaces. No shipking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.
Do not breathe dust/fume/gas/mist/vapors/spray.

IE INHALED: Remove person to fresh air and keep comfortable for breath

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions

| | 011011110u1 2 | - 000.1pt.101.11 | This product is a mixture of the substances herea below with normazaraeas additions. | |
|---|----------------------|--------------------|--|--------|
| | Dangerous | s components: | | |
| | 67-64-1 A | Acetone | | 80.86% |
| Γ | 616-38-6 d | dimethyl carbonate | | 9.14% |
| | 74-98-6 p | propane | | 6.3% |
| | 106-97-8 n | n-butane | | 3.7% |

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a After eye contact:

doctor.

Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting. After swallowing:

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

No further relevant information available. attention needed:

5 Fire-fighting measures

Extinguishing agents: Special hazards: Protective equipment for

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

firefighters: A respiratory protective device may be necessary. Printing date 10/05/2016 Revised On 10/05/2016

Trade name: BRAKE & PARTS CLEANER

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for

containment and cleaning up: Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up. Storage requirements:

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL (United States GHS) Long-term value: 2400 mg/m³, 1000 ppm REL (United States GHS) Long-term value: 590 mg/m³, 250 ppm TLV (United States GHS) Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm

74-98-6 propane

PEL (United States GHS) Long-term value: 1800 mg/m³, 1000 ppm REL (United States GHS) Long-term value: 1800 mg/m³, 1000 ppm TLV (United States GHS) refer to Appendix F inTLVs&BEIs book; NIC-EX

106-97-8 n-butane

REL (United States GHS) Long-term value: 1900 mg/m³, 800 ppm TLV (United States GHS) | Short-term value: (2370) mg/m³, (1000) ppm NIC-EX

Ingredients with biological limit values:

67-64-1 Acetone

BEI (United States GHS) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. **Breathing equipment:**

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Nitrile gloves.

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. -44 °C (-47 °F) **Boiling point:** -19 °C (-2 °F) Flash point: Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

In use, may form flammable/explosive vapour-air mixture. Danger of explosion: Not determined.

Lower Explosion Limit: Upper Explosion Limit: Not determined. 233 hPa (175 mm Hg) Vapor pressure at 20 °C (68 °F):

Between 0.77 and 0.85 (Water equals 1.00) Relative Density:

Vapor density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined. **VOC** content: 529.1 g/l / 4.42 lb/gl

VOC content (less exempt solvents): 10.0 %

(Contd. on page 3)

Safety Data Sheet

Printing date 10/05/2016 Revised On 10/05/2016

Trade name: BRAKE & PARTS CLEANER

(Contd. of page 2) MIR Value: 0.44

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

No dangerous reactions known.

Possibility of hazardous reactions: Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

616-38-6 dimethyl carbonate

LD50 13000 mg/kg (rat)

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

Sénsitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must

be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation:

Completely empty cans should be recycled.

14 Transport information

UN1950 **UN-Number** DOT N/A UN1950

DOT Consumer Commodity ORM-D

Aerosols, flammable 1950 Aerosols

Transport hazard class(es):

Class 2.1

Marine pollutant: No

Special precautions for user: Warning: Gases **EMS Number:** F-D,S-Ù

Packaging Group: UN "Model Regulation":

UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestice Substance List. WHMIS Symbols for Canada:

A - Compressed gas
D2B - Toxic material causing other toxic effects



Page 4/4

Safety Data Sheet

Printing date 10/05/2016 Revised On 10/05/2016

Trade name: BRAKE & PARTS CLEANER

(Contd. of page 3)

EPA:
67-64-1 | Acetone | | |

16 Other information

Contact: Regulatory Affairs 10/05/2016 / -