

BV Series

Specifications

BV5200 SC14 - BV5200 RN



Kubota Models	BV5200 SC14	BV5200 RN
Weight and Dimensions		
Length (in)	187"	187"
Width (in)	99"	99"
Height (in)	111"	111"
Weight (lbs)	7275	7275
Bale chamber		
Diameter Min (in)	24"	24"
Diameter Max (in)	79"	79"
Bale Width(in)	47"	47"
Bale Height(in)	60"	60"
Bale Formation	5 Belts + 3 Rollers	5 Belts + 3 Rollers
Endless Belts	.	.
Bale Ramp	.	.
Pick-up		
Working Width (in)	86"	86"
Number of Tine Rows	5	5
Tine Spacing (in)	2.36"	2.36"
Windguard	Roller Wind Guard	Roller Wind Guard
Pneumatic Gauge Wheel	.	.
Flare to Flare Pickup	86"	
Lift	Hydraulic	
Pickup Protection	Radial Clutch	
Intake System		
Rotar Intake	-	-
Protection, cam clutch	-	-
SuperCut-14 Knives	.	-
Single Knife Protection	.	-
Unblocking System	Hydraulic Drop Floor	Hydraulic Drop Floor
Driveline		
Chain	1.25"	1.25"
1 1/4" Main drive chain	.	.
Wide angle PTO Shaft	.	.
Shear Bolt Protection	-	-
Cam Clutch Protection	.	.
Binding		
Binding	Net/Twine	Net
Monitor	TellusGO	IsoMatch
Twine	double arm	double arm
Operations		
ISOBUS	.	.
IsoMatch	-	.
Tellus PRO	o	o
Hydraulic Outlets	1SA + 1DA	1SA + 1DA
Wheels and Axles		
11.5/80-15	-	-
15.0/55-17	.	.
19.0/45-17	o	o
500/45-22.5	o	o
Others		
PTO (rpm)	540CV	
PTO Protection	CamClutch	
Minimum Horsepower (hp)	70	
Tires	15.0/55-17"	
• = standard o = optional - = not available		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.