

SPECIFICATIONS

| MODEL | L2502 | | L3302 | | L3902 | | L4802 | L4802-Narrow | L4802 | |
|---|---|--|---|--|------------------------------|--|--------------|-------------------------|-------------|-----|
| | Gear-Drive Transmission | | HST | Gear-Drive Transmission | HST | Gear-Drive Transmission | HST | Gear-Drive Transmission | | HST |
| | 2WD | 4WD | 4WD | | | | 2WD | 4WD | 4WD | |
| ENGINE | | | | | | | | | | |
| Type | Direct injection, vertical, water-cooled 4-cycle diesel | | | | | | | | | |
| Engine Gross Power* <i>HP (kW)</i> | 24.8 (18.5) | | 33.0 (24.6) | | 37.5 (28.0) | | 48.4 (36.1) | | | |
| Engine Net Power** <i>HP (kW)</i> | 24.0 (17.9) | | 31.8 (23.7) | | 36.3 (27.1) | | 46.0 (34.3) | | | |
| PTO Power <i>HP (kW)</i> | 20.5 (15.3) | 19.0 (14.2) | 28.0 (20.9) | 26.1 (19.5) | 32.1 (23.9) | 30.3 (22.6) | 40.5 (30.2) | | 39.0 (29.1) | |
| No. of Cylinders | 3 | | | | | | 4 | | | |
| Bore & Stroke <i>in. (mm)</i> | 3.4 × 3.6 (87 × 92.4) | | | 3.4 × 4.0 (87 × 102.4) | | | | | | |
| Total Displacement <i>cu. in. (cm³)</i> | 100.5 (1647) | | 111.4 (1826) | | | | 148.5 (2434) | | | |
| Rated Speed <i>rpm</i> | 2200 | | 2700 | | | | 2600 | | | |
| Battery | 12V, RC: 110 min, CCA: 580 A | 12V, RC: 120 min, CCA: 600 A | 12V, RC: 110 min, CCA: 580 A | 12V, RC: 120 min, CCA: 600 A | 12V, RC: 110 min, CCA: 580 A | 12V, RC: 120 min, CCA: 600 A | | | | |
| Alternator | 12V, 40A | | 12V, 45A | | | | | | | |
| Fuel Tank Capacity <i>US gal. (ℓ)</i> | 11.1 (42) | | | | | | 13.5 (51) | | | |
| PTO | | | | | | | | | | |
| Rear PTO Type | Transmission driven with overrunning clutch | Live-independent hydraulic PTO with PTO brake, wet | Transmission driven with overrunning clutch | Live independent PTO with hydraulic clutch | Live-continuous running | Live independent PTO with hydraulic clutch | | | | |
| PTO/Engine Speed | 540/1910 | 540/2015 | 540/2430 | 540/2470 | 540/2425 | 540/2470 | 540/2475 | | 540/2640 | |
| HYDRAULIC | | | | | | | | | | |
| Lift Control Type | Position control | | | | | | | | | |
| Pump Capacity (main) <i>gpm (ℓ/min)</i> | 5.2 (19.5) | | 6.3 (23.9) | | | | 7.8 (29.4) | | | |
| (PS) <i>gpm (ℓ/min)</i> | 3.1 (11.8) | | 3.8 (14.5) | | | | 4.7 (17.9) | | | |
| 3-Point Hitch | SAE Category I | | | | | | | | | |
| Lift Capacity at Lift Points <i>lbs. (kg)</i> | 1918 (870) | | 1998 (906) | | | | 2870 (1300) | | | |
| 24 in. behind Lift Points <i>lbs. (kg)</i> | 1389 (630) | | 1435 (651) | | | | 2320 (1053) | | | |
| System Pressure <i>kgf/cm² psi</i> | 220 (15.2) | | 165 (16.2) | | | | 180 (17.7) | | | |



* SAE J1995 ** SAE J1349

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

| MODEL | L2502 | | | L3302 | | L3902 | | L4802 | | L4802-Narrow | L4802 | |
|---|---|--|--|--|--|--|--|---|--|--|---|-------------|
| | Gear-Drive Transmission | | HST | Gear-Drive Transmission | HST | Gear-Drive Transmission | HST | Gear-Drive Transmission | | | HST | |
| | 2WD | 4WD | 4WD | 4WD | | | | 2WD | 4WD | | | |
| TRAVELING SYSTEM | | | | | | | | | | | | |
| Transmission | Constant mesh with synchronized shuttle 8 forward and 8 reverse | | Hydrostatic transmission, 3 range speed | Gear shift with synchronized shuttle, 8 forward and 8 reverse | Hydrostatic transmission, 3 range speed | Gear shift with synchronized shuttle, 8 forward and 8 reverse | Hydrostatic transmission, 3 range speed | Constant mesh with synchronized shuttle 8 forward and 8 reverse | | | Hydrostatic transmission, 3 range speed | |
| Steering | Integral type power steering | | | | | | | Hydrostatic power steering | | | | |
| Brake | Mechanical, wet disc type | | | | | | | | | | | |
| Clutch | Dry type single stage | | – | Dry type single stage | – | Dry type dual stage | – | Dry type single stage | | | – | |
| TIRE SIZE | | | | | | | | | | | | |
| AG Standard | Front/Rear | 5.0 - 15 / 11.2 - 24 | | 7.2 - 16 / 11.2 - 24 | | 7.2 - 16 / 11.2 - 24 | | 7.5L - 15 / 14.9 - 24 | 8.3 - 16 / 14.9 - 24 | 7.2 - 16 / 11.2 - 24 | 8.3 - 16 / 14.9 - 24 | |
| TURF Option | Front/Rear | 23 × 8.50-12 / 13.6-16 | | 25 × 8.50-14 / 13.6-16 | | | | 27 × 8.50-15 / 44 × 18-20 | 27 × 10.5-15 / 44 × 18-20 | N/A | 27 × 10.5-15 / 44 × 18-20 | |
| Indust. Option | Front/Rear | N/A | | 27 × 8.50 - 15 / 15 - 19.5 R4 | | | | N/A | 10.0- 16.5 / 17.5L - 24 | N/A | 10.0- 16.5 / 17.5L - 24 | |
| AG/Indust. Hybrid Option | Front/Rear | N/A | | 29 × 9.50-15 / 43 × 16-20 27 × 8.50-15 / 15-19.5 | | | | N/A | | | | |
| Traveling Speed with Standard AG Tires | mph (km/h) | Forward 0.9 (1.4) - 10.7 (17.3) Reverse 0.9 (1.4) - 10.7 (17.2) | Forward 0.0 (0.0) - 11.5 (18.5) Reverse 0.0 (0.0) - 10.3 (16.6) | Forward 1.1 (1.7) - 13.2 (21.2) Reverse 1.1 (1.7) - 13.2 (21.2) | Forward 0.0 (0.0) - 14.1 (22.7) Reverse 0.0 (0.0) - 12.7 (20.5) | Forward 1.1 (1.7) - 13.2 (21.2) Reverse 1.1 (1.7) - 13.2 (21.2) | Forward 0.0 (0.0) - 14.1 (22.7) Reverse 0.0 (0.0) - 12.7 (20.5) | Forward 1.4 (2.2) - 14.9 (24.0) Reverse 1.3 (2.1) - 14.3 (23.0) | Forward 1.2 (1.9) - 12.9 (20.8) Reverse 1.2 (1.9) - 12.4 (20.0) | Forward 0.0 (0.0) - 15.8 (25.4) Reverse 0.0 (0.0) - 14.2 (22.9) | | |
| DIMENSIONS | | | | | | | | | | | | |
| Overall Length (w/o 3P) | in. (mm) | 110.6 (2810) | | 108.5 (2755) | | | | 122.8 (3120) | 120.3 (3055) | 117.7 (2990) | 120.3 (3055) | |
| Overall Width (min. tread) | in. (mm) | 55.1 (1400) | | | | | | | 62.2 (1580) | | 53.7 (1365) | 62.2 (1580) |
| Overall Height (w/Foldable ROPS) | in. (mm) | 91.7 (2330) | | | | | | | | | 94.9 (2410) / 61.2 (1555)*** | 91.7 (2330) |
| Wheelbase | in. (mm) | 63.8 (1620) | | 63.4 (1610) | | | | 72.6 (1845) | | | | |
| Min. Ground Clearance | in. (mm) | 13.6 (345) | | 13.4 (340) | | | | 15.2 (385) | | 11.6 (295) | 15.2 (385) | |
| Tread Front Tire | in. (mm) | 41.3 (1050) | | 43.1 (1095) | | | | 50.4 (1280) / 54.3 (1380) / 58.3 (1480) / 62.2 (1580) | 45.5 (1155) | 39.4 (1000) | 45.5 (1155) | |
| Tread Rear Tire | in. (mm) | 43.9 (1115) / 47.1 (1195) / 50.8 (1290) | | | | | | 46.5 (1180) / 47.2 (1200) / 51.2 (1300) / 57.1 (1450) / 60.8 (1545) | 41.3 (1050) | | 46.5 (1180) / 47.2 (1200) / 51.2 (1300) / 57.1 (1450) / 60.8 (1545) | |
| Min. Turning Radius (w/brake, 4WD disengaged) | feet (m) | 7.9 (2.4) | | 8.2 (2.5) | | | | 8.9 (2.7) | 8.5 (2.6) | 8.9 (2.7) | 8.5 (2.6) | |
| Weight (with ROPS) | lbs. (kg) | 2601 (1180) | 2811 (1275) | 2833 (1285) | 2734 (1240) | 2778 (1260) | 2767 (1255) | 2778 (1260) | 3296 (1495) | 3428 (1555) | 3362 (1525) | 3549 (1610) |