

# Specifications

Model	M4D-061HDC12	M4-071HDC12	M4D-071HDC12
CAB	4WD Deluxe Wide Cab	4WD Standard Wide Cab	4WD Deluxe Wide Cab
<b>Engine</b>	V3307-CR-TE4		
Type (Make : KUBOTA)	4 cylinder in-line, Common Rail System, Direct Injection		
No. of cylinders/Aspiration	4 / turbocharged		
Engine gross power (97/68/EC) HP (kW)	65.4 (48.8)		73.2 (54.6)
PTO power (at rated engine rpm) HP (kW)	52 (38.8)		60 (44.7)
Total displacement cu.in. (cc)	203 (3331)		
Rated engine RPM	2400		
Fuel tank capacity gal. (ℓ)	23.8 (90)		
Alternator Amp	130		
<b>Transmission</b>			
No. of speeds	F12 / R12 (option: F18 / R18 with Creep)		
Main gear shift	Fully synchronized (6 speed)		
Shuttle shift	Hydraulic-shuttle		
Main clutch type	Multiple wet disc		
Brake type	Hydraulic wet disc		
Differential lock (Front / Rear)	Limited Slip Differential / Mechanical		
4WD clutch type	Electro-hydraulic on-the-go	Mechanical on-the-go	Electro-Hydraulic on-the-go
<b>PTO</b>			
Type	Live-independent PTO, electro-hydraulic clutch with brake		
Speed rpm	540 / 540E	540 (540 / 540E: OPT)	540 / 540E
<b>Hydraulics</b>			
Pump capacity (3-Point Hitch) gpm (ℓ/min.)	16.7 (63.3)		
3-Point Hitch	Telescopic lower link ends, Telescopic Stabilizers		
Category	I / II		
Control system	Position, draft (top link sensing) & mixed control		
Lift capacity at 24 in. behind lift point (ASAE) lbs. (kg)	3307 (1500)		
Cylinder type	Two external cylinders		
No. of standard remote valves	2 (SCD / FD), Max. 3	1 (SCD), Max. 3	2 (SCD / FD), Max. 3
<b>Other features</b>			
4WD system	Bevel gear type		
Steering	Hydrostatic power steering		
Tilt steering	Standard		
Hood type / Pedal type	Full open, slanted, steel / Hanging		
Deck type (ISO-mounted w/rubber mat)	Full-flat		
Panel type	Electronic		
<b>Standard tire size</b>			
Front	320 / 85R20		
Rear	420 / 85R30		
<b>Dimensions &amp; weight</b>			
Overall length in. (mm)	142 (3600)		
Overall height top of CAB in. (mm)	101 (2560)		
Overall width (minimum) in. (mm)	75.6 (1920)		
Wheelbase in. (mm)	84.1 (2135)		
Crop clearance (Front axle) in. (mm)	18.1 (460)		
Tread width Front in. (mm)	58.5 (1487)		
Tread width Rear in. (mm)	56.2, 68.7 (1430, 1744)		
Turning radius (w/o brake) ft. (m)	11.8 (3.6)		
Tractor weight lbs. (kg)	6008 (2725)	5952 (2700)	6008 (2725)

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



## KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: [kubotaUSA.com](http://kubotaUSA.com)

©2019 Kubota Corporation



**Kubota**  
**Genuine Parts**  
for maximum performance, durability and safety