

# Specifications

Model		M6H-101	
		SHD	
		4WD	
Engine			
Type (make: Kubota)		V3800-TIEF4-Direct Injection, Water-cooled 4 Cycle Diesel, Common Rail System, Turbocharger, Intercooler, DPF, DOC, SCR	
Cylinders and displacement	cu. in. (cc)	4-cylinder, 230 (3769)	
Engine gross power (97/68EC)	HP (kW)	104.4 (77.9)	
PTO power (at rated RPM)	HP (kW)	84.0 (62.6)	
Alternator	Amp	80	
Rated engine speed	rpm	2600	
Fuel tank capacity	gal. (ℓ)	46 (175)	
Transmission			
No. of speeds	Standard	F24 / R24 (with creep)	
Traveling speed	mi/h (km/h)	0.11 – 16.37 (0.18 – 26.34)	
Shuttle		Electro-hydraulic	
Clutch		Hydraulic Wet Clutch	
Rear wheel brake		Hydraulic Wet Disk Type	
Mechanical differential lock		Front / Rear	
PTO			
Clutch		Hydraulic Wet Clutch	
Revolution	rpm	540 (540/1000 option)	
Hydraulics			
Type		Open-Center	
Draft control		Top Link Draft Sensing	
Lift capacity at 24 in. behind lift point (OECD)	lbs. (kg)	3858 (1750), 5732 (2600) with 2 assist cylinders (option)	
Lower link		Telescopic	
Category		II	
Rear remotes		2 standard (3rd & flow control valve optional)	
Pump output (remote)	gal/min (ℓ/min)	17.6 (66.6)	
Exterior			
Hood		Full-open	
Dimensions			
Wheel base	in. (mm)	95.3 (2420)	
Minimum ground clearance*	in. (mm)	25.8 (655)	
Tread*	Front	in. (mm) 61.6, 65.6, 72.0, 75.8, 79.7 (1565, 1665, 1830, 1925, 2025)	
	rear	in. (mm) 60.8, 64.8, 73.4, 77.2, 81.1 (1545, 1645, 1865, 1960, 2060)	
Overall length	in. (mm)	168.3 (4275)	
Overall height (ROPS unfolded)	in. (mm)	111.6 (2835)	
Overall width	in. (mm)	79.9 (2030)	
Weight	lbs. (kg)	8157 (3700)	
Turning radius w/o brake	ft. (m)	21.0 (6.4)	
Standard tires	Front	13.6-38	
	rear	13.6-38 (steel)	

\* When standard tires are equipped

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



©2017 Kubota Corporation

# Kubota

**KUBOTA TRACTOR CORPORATION**

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: [KubotaUSA.com](http://KubotaUSA.com)

